

General Information

- **Model:** Power Mulcher 200
- **Manufacturer:** Drizzonti Srl
- **Application:** Pruning and mulching in orchards vineyards, and citrus groves
Maximum Cutting Diameter: 8-10 cm

Dimensions & Weight

- **Working Width:** 200 cm
- **Overall Dimensions (L×W×H):** 220 × 105 × 46 cm
- **Weight:** 725 kg

Tractor Requirements

- **Recommended Power:** 40-100 hp
- **Three-Point Hitch Category:** CAT II-III
- **PTO Speed:** 540 rpm



Construction & Features

- **Frame:** Double-reinforced 10 mm steel structure
- **Side Design:** Bevelled and rounded sides (46 cm height) to prevent plant damage
- **Large Rear Roller:** Adjustable for varying working heights
- **Stone Protection:** Rear rubber guard
- **Transmission:** Gearbox with freewheel and 3-5 external toothed belts
- **Lateral Displacement:** 10 cm hydraulic adjustment
- **Attachment:** Three-point hitch with adjustable slots for flexibility

Cutting System

- **Hammers:** Ø 20 mm, 1.5 kg each
- **Knives:** Ø 20 mm
- **Counter-Knives:** 3 rows of "U" shaped knives with internal toothed profile

Optional Equipment

- **Speed Green Head:** For under-plant maintenance, operable via tractor hydraulics or an independent tank

- Best Finish and Finest Mulch -

ST1

Single side application on shredder



MODEL



\$ excl

ST1

The range of

4kg **\$14,900**

shredders is enriched with some interesting side applications for processing along the row, available on our VIP- STAR-POWER models, for double machining in a single step, ensuring savings in time and important costs.

Rounding branches, applied laterally to the shredder with mechanical adjustment closing the head on the shredder itself. Hydraulic motor with quick-coupling pipes to the tractor, thanks to the reduced height of the gyroscopes, it is possible to work under the plant even with fruit hanging. Required 20/25 lt/min.

The series also includes cross-wire grass cutter heads, in single and double version thanks to our terminal tools mod. Speed Green & Ecology available in different working sizes (30-60-80 cm). For both solutions are available versions with direct oil demand to the tractor or autonomous systems complete with: oil, heat exchanger, filter, level indicator and hydraulic pumps, all controlled by an electro-hydraulic kit box.

www.agtek.co.nz
sales@agtek.co.nz
 Ph: 021 0202 0202

AGTEK
 TRACTORS & EQUIPMENT